

Workingload of the cable holder for all types in kg

High tensil cable, DIN EN 12385-4, 7x7, 2300 N / mm²

Cable Holder type -with TÜV / GS certification	cable-ø in mm										
	0,45	0,54	0,63	0,81	1,0	1,2	1,5	1,8	2,0	2,5	3,0
10	-	-	-	8	11	-	-	-	-	-	-
12	-	-	-	-	13	16	-	-	-	-	-
15	-	-	-	-	13	16	25	-	-	-	-
18	-	-	-	-	12	20	29	34	-	-	-
18 S	-	-	-	-	14	24	34	40	-	-	-
20	-	-	-	-	12	20	29	34	55	-	-
20 S	-	-	-	-	14	24	34	40	66	-	-
25	-	-	-	-	-	-	24	42	56	68	-
30	-	-	-	-	-	-	-	-	-	70	85
30 S	-	-	-	-	-	-	-	-	-	84	102

Stainless steel cable DIN EN 12385-4, 7x7, 1570 N / mm²

10	1,5	2,5	3,0	7	10	-	-	-	-	-	-
12	-	-	-	-	8	12	-	-	-	-	-
15	-	-	-	-	8	12	16	-	-	-	-
18	-	-	-	-	7	10	16	30	-	-	-
18 S	-	-	-	-	8	12	19	36	-	-	-
20	-	-	-	-	7	10	16	30	38	-	-
20 S	-	-	-	-	8	12	19	36	44	-	-
25	-	-	-	-	-	-	23	30	35	42	-
30	-	-	-	-	-	-	-	-	-	50	70
30 S	-	-	-	-	-	-	-	-	-	60	84

S = six-ball-mechanism